



Weight : 7 g

CN1 : Pin Assignment
12505WS-06 (Yeonho)

Pin No.	Input / Output
1	DC +12V IN
2	GND
3	Video Out
4	GND
5	Line Lock
6	GND

Mate with 12505HS-06 (Yeonho)

CN2 : Pin Assignment
12505WS-04 (Yeonho)

Pin No.	IR LED
1	CDS
2	IR LED
3	GND
4	DC +12V

Mate with 12505HS-04 (Yeonho)

CN4 : Pin Assignment
12505WS-04 (Yeonho)

Pin No.	DC IRIS
1	DMP -
2	DMP +
3	DRV +
4	DRV -

Mate with 12505HS-04 (Yeonho)

CN5 : Pin Assignment
12505WS-07 (Yeonho)

Pin No.	OSD
1	OSD KEY
2	GND
3	N.C.
4	N.C.
5	N.C.
6	N.C.
7	N.C.

Mate with 12505HS-07 (Yeonho)

CN6 : Pin Assignment
BM05B-SRSS-TB (JST)

Pin No.	Serial
1	GND
2	N.C.
3	RX232
4	TX232
5	+3.3V

Mate with SHR-05V-S (JST)

CN3 : Pin Assignment
12505WS-02 (Yeonho)

Pin No.	DN Drive
1	MT +
2	MT -

Mate with 12505HS-02 (Yeonho)

※ RoHS Compliance

③				Designed by	Checked by	Approved by	Angle	Material	Drawing Name												
									PA-31x Dim.(Tentative)												
									Tolerance	Color(Finish)	Parts Code NO.	Drawing NO.									
②				2014/12/15 T.Fujihira			<table border="1"> <tr> <td>L ≤ 30</td> <td>+0.1</td> </tr> <tr> <td>30 < L ≤ 50</td> <td>+0.15</td> </tr> <tr> <td>50 < L ≤ 100</td> <td>+0.2</td> </tr> <tr> <td>100 < L ≤ 200</td> <td>+0.3</td> </tr> <tr> <td>200 < L ≤ 300</td> <td>+0.4</td> </tr> <tr> <td>300 < L</td> <td>+0.5</td> </tr> </table>	L ≤ 30	+0.1	30 < L ≤ 50	+0.15	50 < L ≤ 100	+0.2	100 < L ≤ 200	+0.3	200 < L ≤ 300	+0.4	300 < L	+0.5		02-A0382-00-00
L ≤ 30	+0.1																				
30 < L ≤ 50	+0.15																				
50 < L ≤ 100	+0.2																				
100 < L ≤ 200	+0.3																				
200 < L ≤ 300	+0.4																				
300 < L	+0.5																				
①							Scale	Project Name													
No.	1	2	3	4	5	6	7	8													

1

2

3

4

5

6

7

8